





		State and a		
All-In-C	One Integrated Sola	r Street Light (80W)	Model: BR-AIO80W	
Solar Panel	Max Power	18V100W (High Efficiency Monocrystalline Silicon)		
	LifeTime	25 Years		
Battery	Type	12.8V/60Ah Lithium Battery		
	Life Time	5 Years		
LED Lamp (No sensor)	Max Power	12V 80W		
	LED Chip Brand	Bridgelux from USA with High Brightness		
	Lumen (LM)	8000-8500LM		
	Life Time	50000 Hours		
	Viewing Angle	120°		
Charge Time	by Sun	6 Hours (with Enough Strong Shine)		
Discharge Time	Working M ode	100% efficiency 6hrs 50% efficiency 3hrs 30% efficiency 3hrs		
		12hours per day.(5days continuour	rs working when meet rainy days)	
working Temperature	Range(°C)	-30°C~+70°C		
Colour Temperature	Range(K)	6000K		
Pole Height	Range (M)	8-12M		
Space Between Light	Range (M)	20-40M		
Main Material of Lamp	Aluminium Alloy			
Certificate	CE / ROHS / IP65 /IES			
Warranty Period	2 Years	ears		
Packing & Weight	Product Size	1200*450*140mm		
	N. W/G. W.	20kg/24kg		
	Carton Size	1320*550*220mm		
	Q'ty/CTN	1 Set/CTN		
Packs Containers	20' GP	200 Sets		
	40' GP	400 Sets		